

# Technical Data Sheet

## Q 40-600 Rust Converter Aerosol

### Characteristics:

Rust converter and epoxy primer in one. For all vehicles. Simply spray the transparent active substance directly onto the rust. Remove loose rust first. The rust is turned into a black-grey protective coat that can be covered with a 1K topcoat when dry. Effective rust repairs for all metal plates, ferrous metals and steel.

### Application:

For effective rust conversion and simultaneous priming of metal surfaces such as steel, steel plate, ferrous metals etc. The rust turns into a black-grey layer and rust is repaired. The area can be painted over with 1K topcoats (colour shade) once dry.

### Note:


Before starting work, clean the surface or object that is to be painted and remove all grease. Remove loose rust! Do not spray onto synthetic resin coated surfaces because the paint may lift.

### Technical data:


Base: Special resins




Clean surface




2 min.



10 - 20 cm  
3-4 x 20 - 30  $\mu$



paintable: 24 h



Shelf life



Store in cool place



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

Copyright: Q-Company 2017, all rights reserved.

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany

Version: 02.01.2017