

# Technical Data Sheet

## Q 50-185 HS Acrylic Tape


### Characteristics:

Q 50-180 HS Acrylic Tape is a reinforced acrylic foam tape with high tack and shear strength performance acrylic adhesive. The product has excellent resistance to solvent, chemical, UV and heat, making the tape bond securely to a very wide range of substrates. Ideal for bonding emblems, nameplates and metal.

### Technical Data:

Values shown are typical values and not to be used for specification purposes.

Carrier	Acrylic Foam Base in Clear
Liner	Red HDPE
Adhesive	High Tack Acrylic (Solvent Based)
Thickness	0.5mm and 1mm (+/- 0.05mm) Clear only.
Width	9mm, 12mm, 19mm and 25mm (+/- 1mm)
Length	10m (+/- 0.1m)
Peel Adhesion	PSTC-3 2.8kgs/25mm
Shear Strength	PSTC-7 over 72 hours with 2kg on 25mm x 25mm at 25°C
Tensile Strength	Over 50kgs/25mm x 25mm
Heat Resistance	PSTC-9 over 24 hours with 1kg on 25mm x 25mm at 80°C
Service Temperature	-40°C to 170°C
Application Temperature	-10°C to 150°C



Shelf life



Store in  
dry and cool place

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

Copyright: Q-Company 2017, all rights reserved.

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany

Version: 02.01.2017