Safety data sheet according to 1907/2006/EC, Article 31



Revision: 28.01.2022

Printing date 28.01.2022

Version number 61

SECTION 1: Identification of the substance/mixture and of the company/

1.1 Product ide	entifier	
1.2 Relevant io No further relev	<u>Mipa 2K-Beschleuniger</u> dentified uses of the substance or mixture and uses advised against vant information available. f the substance / the mixture Accelerator	
	the supplier of the safety data sheet	
Manufacturer/S MIPA SE	Supplier:	
Am Oberen Mo		
D-84051 Essen Tel.: +49(0)870		
Fax.: +49(0)870 Fax.: +49(0)870		
	iistratur@mipa-paints.com	
www.mipa-pain 1.4 Emergency	nts.com y telephone number: International emergency number: +49(0)700 24112112 (MIF
- 55		
SECTION 2	: Hazards identification	
	tion of the substance or mixture according to Regulation (EC) No 1272/2008	
flame	,	
\checkmark		
Flam. Liq. 3	H226 Flammable liquid and vapour.	
health	h hazard	
Muta. 2	H341 Suspected of causing genetic defects.	
Repr. 1B	H360FD May damage fertility. May damage the unborn child.	
STOT SE 2	H371 May cause damage to organs.	
STOT RE 2	H373 May cause damage to the immune system through prolong repeated exposure.	ed
	sion	
🔟 🖑 corros		
Eye Dam. 1	H318 Causes serious eye damage.	
Eye Dam. 1		
Eye Dam. 1	H318 Causes serious eye damage. onment	
Eye Dam. 1	onment	
Eye Dam. 1	onment c 2 H411 Toxic to aquatic life with long lasting effects. H315 Causes skin irritation.	
Eye Dam. 1 enviro Aquatic Chronic Skin Irrit. 2	onment c 2 H411 Toxic to aquatic life with long lasting effects. H315 Causes skin irritation.	

according to 1907/2006/EC, Article 31



Printing date 28.01.2022

Version number 61

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 1)

· 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS02 GHS05 GHS07 GHS08 GHS09 · Signal word Danger · Hazard-determining components of labelling: n-Butvl acetate dibutyltin dilaurate · Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H341 Suspected of causing genetic defects. H360FD May damage fertility. May damage the unborn child. H371 May cause damage to organs. H336 May cause drowsiness or dizziness. H373 May cause damage to the immune system through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition P210 sources. No smoking. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P321 Specific treatment (see on this label). P362+P364 Take off contaminated clothing and wash it before reuse. · Additional information: Restricted to professional users. 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate line Flam. Liq. 3, H226; (1) STOT SE 3, H336	50-100%		
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	dibutyltin dilaurate	<u>≥</u> 3-<5%		
(Contd. on pac				

according to 1907/2006/EC, Article 31

Printing date 28.01.2022

Version number 61



Revision: 28.01.2022

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Generally the product does not irritate the skin. Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

GB

according to 1907/2006/EC, Article 31



Revision: 28.01.2022

Printing date 28.01.2022

Version number 61

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 3)

Open and handle receptacle with care. Prevent formation of aerosols.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Store away from foodstuffs.

- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

77-58-7 dibutyltin dilaurate

WEL Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn; Sk

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

according to 1907/2006/EC, Article 31



Version number 61

Professional Coating Systems

Revision: 28.01.2022

Trade name: Mipa 2K-Beschleuniger

Material of gloves

(Contd. of page 4)

GB

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and c	9.1 Information on basic physical and chemical properties				
General Information					
Appearance:					
Form:	Fluid				
Colour:	According to product specification Characteristic				
Odour: Odour threshold:	Not determined.				
pH-value:	Not determined.				
Change in condition					
Melting point/freezing point:	Undetermined.				
Initial boiling point and boiling range:	124 °C				
Flash point:	23 °C (DIN 53213)				
Flammability (solid, gas):	Not applicable.				
Ignition temperature:	370 °C (DIN 51794)				
Decomposition temperature:	Not determined.				
Auto-ignition temperature:	Product is not selfigniting.				
Explosive properties:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.				
Explosion limits:					
Lower:	1.2 Vol %				
Upper:	7.5 Vol %				
Vapour pressure at 20 °C:	10.7 hPa				
Density at 20 °C:	0.884 g/cm³ (DIN 53217)				
Relative density	Not determined.				
Vapour density	Not determined.				
Evaporation rate	Not determined.				
Solubility in / Miscibility with					
water:	Not miscible or difficult to mix.				
Partition coefficient: n-octanol/water:	Not determined.				
Viscosity:					
Dynamic:	Not determined.				
Kinematic at 20 °C:	15 s (DIN 53211/4)				

according to 1907/2006/EC, Article 31



Revision: 28.01.2022

Printing date 28.01.2022

Version number 61

Trade name: Mipa 2K-Beschleuniger

	(Contd	. of page 5)
 Solvent content: VOC (EC) 	97.00 %	
Solids content (weight-%):	3.0 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

123-86-4 n-Butyl acetate

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rabbit)

- Primary irritant effect: Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
- Causes serious eye damage.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction. • Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity
- Suspected of causing genetic defects.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- May damage fertility. May damage the unborn child.
- STOT-single exposure
- May cause damage to organs.
- May cause drowsiness or dizziness.
- STOT-repeated exposure
- May cause damage to the immune system through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

• **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 7)

GB

according to 1907/2006/EC, Article 31



Revision: 28.01.2022

Printing date 28.01.2022

Version number 61

Trade name: Mipa 2K-Beschleuniger

· **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. of page 6)

- **12.4 Mobility in soil** No further relevant information available.
- · Ecotoxical effects:
- Remark: Toxic for fish
- Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.



according to 1907/2006/EC, Article 31



Revision: 28.01.2022

Printing date 28.01.2022

Version number 61

Trade name: Mipa 2K-Beschleuniger

	(Contd. of page
Label	3
ΊΑΤΑ	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
ADR, IMDG, IATA	<i>III</i>
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: dibutyltin dilaurate
[.] Marine pollutant:	No
	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
EMS Number:	F-E, <u>S-E</u>
· Segregation groups · Stowage Category	Acids A
14.7 Transport in bulk according to Annex II	
of Marpol and the IBC Code	Not applicable.
• Transport/Additional information:	
ADR	
· Limited quantities (LQ)	5L
· Transport category	3
Tunnel restriction code	D/E
· Remarks:	≤ 5 l: 2.2.3.1.5 ADR
· IMDG	
· Limited quantities (LQ)	5L
· Remarks:	≤ 450 l: 2.3.2.5 IMDG
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t • Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 9)

GB

according to 1907/2006/EC, Article 31

Professional Coating Systems

Revision: 28.01.2022

Printing date 28.01.2022

Version number 61

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 8)

• National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

50-100 NK

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- Flammable liquid and vapour. H226
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- May cause drowsiness or dizziness. H336
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H370 Causes damage to organs.
- Causes damage to organs through prolonged or repeated exposure. H372
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids Category 3 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- Skin Sens. 1: Skin sensitisation Category 1 Muta. 2: Germ cell mutagenicity - Category 2
- Repr. 1B: Reproductive toxicity Category 1B
- STOT SE 1: Specific target organ toxicity (single exposure) Category 1
- STOT SE 2: Specific target organ toxicity (single exposure) Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- STOT RE 1: Specific target organ toxicity (repeated exposure) Category 1
- STOT RE 2: Specific target organ toxicity (repeated exposure) Category 2
- Aquatic Acute 1: Hazardous to the aquatic environment acute aquatic hazard Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment long-term aquatic hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2
- ** Data compared to the previous version altered.